



# Spec Sheet Model 8760



Model	8760						
	Headquarters/Data Center						
Aggregate Bandwidth	200 Mbps	500 Mbps	1 Gbps	2 Gbps	3 Gbps	4 Gbps	5 Gbps
Full Duplex License Bandwidth	100 Mbps	250 Mbps	500 Mbps	1 Gbps	1.5 Gbps	2 Gbps	2.5 Gbps
Device Throughput (Gbps)*	10	10	10	10	10	10	10
Max. Concurrent Flows	2,048,000	2,048,000	2,048,000	2,048,000	2,048,000	2,048,000	2,048,000
Packets Per Second	100,000	100,000	150,000	300,000	400,000	500,000	600,000
L7 Connection Rate (Max/Sec)	6,000	6,000	6,000	15,000	20,000	25,000	30,000
PDF Reports	80	80	80	80	80	80	80
SLAs	250	250	250	250	250	250	250
ARM Objects	30	40	50	50	50	50	50
Policies	2,048	2,048	2,048	2,048	2,048	2,048	2,048
<b>Hardware</b>							
Network Interfaces	Total 6 2x 10/100/1000 Base-T (Bypass), 4x 10/100/1000 Base-T						
Ethernet Bypass Pairs	Default 1 (Max 8)						
Network Expansion (Optional)	4 Slots (3 Free)						
Console Port	RS-232 male DB-9						
Dual Power Supplies	2 (Energy Smart Power Supply Redundant)						
RAID HDD	Yes (RAID 10)						
Hot Swap Disks	Yes						
Weight	26.1 kg / 57.52 lb						
Form Factor / Dimensions (w x h x d)	19" Rack Mount (2 RU) / 17.44" x 3.40" x 26.80"						
Rack Mount Rails	Sliding Ready Rails with Cable Management Arm						
<b>Power &amp; Environment</b>							
Power	Auto Ranging (100V~240V)						
Environment	Relative Humidity 0-90% (Non-condensing)						
Approvals	CE, FCC Certified / RoHS						

\* Default configuration 1 Gbps copper interface card, expandable to 10 Gbps copper or fiber interface cards



North America  
+1 877 439 4632

EMEA  
+44 808 120 1996

Asia Pacific  
+61 3 9415 8332

[www.exinda.com](http://www.exinda.com)